

CLAIMS

What is claimed is:

1. A memory subsystem comprising
two memory devices connected in parallel to a bus,
said bus including a plurality of bus lines for
5 carrying substantially all address, data and control in-
formation needed by said memory devices,
said control information including device-select
information,
said bus containing substantially fewer bus lines than
10 the number of bits in a single address, and
said bus carrying device-select information without the
need for separate device-select lines connected directly to
individual memory devices.
- 15 2. The memory subsystem of claim 1 wherein said bus
contains at least 8 bus lines adapted to carry at least 16
address bits and at least 8 data bits.
- 20 3. The memory subsystem of claim 1 wherein said bus also
includes parallel lines for clock and power.
4. A system comprising
a memory subsystem of claim 1 wherein each bus of said
memory subsystem is connected to its own transceiver device,

a transceiver bus connecting said transceiver devices,
and

a means for transferring information between each of
said buses of said memory subsystems and said transceiver
bus, whereby memory subsystems may be integrated into a
larger system having more memory than an individual memory
subsystem.

5. The system of claim 4 having a plurality of memory
subsystems.

6. The system of claim 4 further comprising a master
device connected to said transceiver bus.

7. The system of claim 6 wherein said master device is
selected from the group consisting of a central processing unit,
a floating point unit and a direct memory access unit.

8. The system of claim 4 further comprising a peripheral
device connected to the transceiver bus, said peripheral device
adapted for connection to other devices not on the bus.

9. The system of claim 8 wherein said peripheral device is
selected from the group consisting of an I/O interface port, a
video controller and a disk controller.

10. The system of claim 5 wherein said transceiver bus is in a different plane than the plane of the bus of each of said memory subsystems.

5

11. The system of claim 5 wherein the bus of each memory subsystem lies substantially in a subsystem bus plane and said transceiver bus lies substantially in a plane orthogonal to said subsystem bus plane.

10

12. The system of claim 4 having at least two transceiver buses, each transceiver bus having a plurality of memory subsystem buses connected through a first transceiver to said transceiver bus,

15

each of said transceiver buses being further connected to a second transceiver adapted to interface to a second-order transceiver bus, whereby each transceiver bus is connected through said second transceiver to form a second-order transceiver bus unit.

20

13. A semiconductor subsystem bus for interconnecting semiconductor devices comprising

a plurality of semiconductor devices connected in parallel to a bus, at least one of said semiconductor

devices being a memory device or a transceiver device which in turn is connected to a memory subsystem,

said bus including a plurality of bus lines for carrying substantially all address, data and control information needed by said semiconductor devices,

said control information including semiconductor device-select information,

said bus containing substantially fewer bus lines than the number of bits in a single address, and

said bus carrying device-select information without the need for separate device-select lines connected directly to individual semiconductor devices, and

at least one modifiable register in each of the semiconductor devices on said bus, said modifiable registers being accessible from said bus, whereby the subsystem can be configured using signals transmitted on said bus.

14. The semiconductor subsystem bus of claim 13 wherein one type of modifiable register is an access-time register designed to store a time delay after which a device may take some specified action on said bus.

15. The semiconductor subsystem bus of claim 13 further comprising a semiconductor device having at least two access-time registers and

one of said access-time registers is permanently programmed to contain a fixed value and at least one of said access-time registers can be modified by information carried on said bus.

5 16. The semiconductor subsystem bus of claim 13 further comprising a memory device having at least one discrete memory section and also having a modifiable address register adapted to store memory address information which corresponds to each said discrete memory section.

10 17. The semiconductor subsystem bus of claim 16 wherein said memory address information comprises a pointer to said discrete memory section.

15 18. The semiconductor subsystem bus of claim 16 wherein said discrete memory section has a top and a bottom and said memory address information comprises pointers to said top and said bottom.

20 19. The semiconductor subsystem bus of claim 16 wherein said memory address information comprises
 a pointer to said discrete memory section and
 a range value indicating the size of said discrete
 memory section.

25

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

20. The semiconductor subsystem bus of claim 16 wherein said address registers of each of said discrete memory sections of each of said memory devices connected to said bus are set to contain memory address information that is different for each discrete memory section and such that the highest memory address in each discrete memory section is one less than the lowest memory address in another discrete memory section,

whereby memory may be organized into one or a small number of contiguous memory blocks.

21. The semiconductor subsystem bus of claim 16 further comprising a means for testing each of said discrete memory sections of each of said memory devices for proper function, and

for each non-functional discrete memory section, a means for setting at least one address register which corresponds to said discrete memory section to indicate that said discrete memory section is non-functional, ,

for each functional discrete memory section, a means for setting at least one address register which corresponds to said discrete memory section to contain such corresponding address information.

22. The semiconductor subsystem bus of claim 21 wherein said address registers corresponding to said discrete memory

sections are set to provide one contiguous memory block within the subsystem.

23. The semiconductor subsystem bus of claim 13 wherein one of said modifiable registers is a device identification register which can be modified to contain a value unique to that semiconductor device.

24. The semiconductor subsystem bus of claim 23 wherein said device identification register is set to contain a unique value which is a function of the physical position of that semiconductor device either along said bus or in relationship to other semiconductor devices or said bus.

25. A bus subsystem comprising

two semiconductor devices connected in parallel to a bus, wherein one of said semiconductor devices is a master device,

said master device including a means for initiating bus transactions,

said bus including a plurality of bus lines for carrying substantially all address, data and control information needed by said devices,

said control information including device-select information,

said bus containing substantially fewer lines than the number of bits in a single address, and

said bus carrying device-select information without the need for separate device-select lines connected directly to individual devices on said bus, whereby said master device initiates bus transactions which transfer information between said semiconductor devices on said bus.

26. The bus subsystem of claim 25 wherein one of said semiconductor devices is a memory device connected to said bus, said memory device having at least one discrete memory section and also having a modifiable address register adapted to store memory address information which corresponds to each said discrete memory section.

27. The bus subsystem of claim 26 wherein one of said semiconductor devices comprises a transceiver device connected in parallel to said bus and connected in parallel to a memory device on a bus other than said bus.

28. The bus subsystem of claim 26 further including a means for said master device to request said memory device to prepare for a bus transaction by sending a request packet along said bus, said memory device and said master device each having a device-internal means to prepare to begin said bus transaction during a

device-internal phase and further having a bus access means to effect said bus transaction during a bus access phase, said request packet including

5 a sequence of bytes containing address and control information,

said control information including information about the requested bus transaction and about the access time, which corresponds to a number of bus cycles, which needs to intervene before beginning said bus-access phase, and

10 said address information pointing to at least one memory location within one of said discrete memory sections of said memory device.

29. The bus subsystem of claim 28 wherein said memory device includes a means to read said control information and initiate said device-internal means at a time so as to complete said device-internal phase within said access time and begin said bus access phase after said number of bus cycles.

20 30. The bus subsystem of claim 28 wherein said control information comprises an op code.

31. The bus subsystem of claim 30 wherein said memory device includes sense amplifiers adapted to hold a bit of information or to precharge after a selected time and a means to

transfer a data block during a data block transfer either reading data from said memory device or writing data into said memory device, and

wherein said op code instructs said memory device to
5 activate a response means, said response means including a means to

initiate a data block transfer,
select the size of said data block,
select the time to initiate said data block transfer,
10 access a control register, including reading from or
writing to said control register,
precharge said sense amplifiers after each of said data
block transfers is complete,
hold a bit of information in each of said sense
15 amplifiers after each of said data block transfers is
complete, or
select normal or page-mode access.

32. The bus subsystem of claim 31 wherein said data block
20 transfer comprises a read from or a write to memory within a
single memory device.

33. The bus subsystem of claim 28 further comprising a
means for said master device to send control information to a
25 specific one of said semiconductor devices on said bus by

including in said request packet a device identification number unique to said semiconductor device.

5 34. The bus subsystem of claim 28 further comprising a means for said master device to send control information to a selected one of said discrete memory portions by including in said request packet a specific memory address.

10 35. The bus subsystem of claim 28 further comprising a means for said master device to send control information to substantially all semiconductor devices on said bus by including in said request packet a special device identification number which is recognized by said semiconductor devices.

15 36. The bus subsystem of claim 28 wherein said control information specifies directly or indirectly the number of bus cycles for said master device and said memory device to wait before beginning said bus access phase.

20 37. The bus subsystem of claim 36 wherein, for a data block transfer, said master device and said memory device use the same access time and same data block size regardless of whether said data block transfer is a read or write operation.

38. The bus subsystem of claim 28 wherein said control information further includes a block-size value that encodes and specifies the size of the block of data to be transferred.

5 39. The bus subsystem of claim 38 wherein said block-size value is encoded as a linear value for relatively small block sizes values and is encoded as a logarithmic value for relatively larger block sizes.

10 40. The bus subsystem of claim 38 wherein said block-size value is encoded using four bits, and where the encoded value is

15
20
25
30

| <u>Encoded Value</u> | <u>Block Size (Bytes)</u> |
|----------------------|---------------------------|
| 0 | 0 |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| 4 | 4 |
| 5 | 5 |
| 6 | 6 |
| 7 | 7 |
| 8 | 8 |
| 9 | 16 |
| 10 | 32 |
| 11 | 64 |
| 12 | 128 |
| 13 | 256 |
| 14 | 512 |
| 15 | 1024 |

41. The bus subsystem of claim 26 wherein said memory device is a DRAM device containing
35 a plurality of sense amplifiers,

a means to hold said sense amplifiers in an unmodified state after a read or write operation, leaving the device in page mode,

a means to precharge said sense amplifiers and

5 a means for selecting whether to precharge said sense amplifiers or to hold said sense amplifiers in an unmodified state.

10 42. The bus subsystem of claim 28 wherein said request packet comprises an even number of bytes.

15 43. The bus subsystem of claim 28 further including a means for generating and controlling a plurality of bus cycles, during which said bus carries said address, data and control information, and wherein alternate said bus cycles are designated odd cycles and even cycles, respectively, and wherein said request packet begins only on an even cycle.

20 44. The bus subsystem of claim 28 further including a means for generating ECC information corresponding to a block of data and a means for using said ECC information to correct errors in storing or reading said block of data, wherein said ECC information may be stored separately from said block of data.

45. The bus subsystem of claim 44 further comprising at least two of said memory devices wherein said ECC information and said corresponding block of data are stored in a first and a second said memory device, respectively, and said master device includes a means to write or read said block of data with error correction by sending separate ones of said request packets for said ECC information and for said corresponding block of data.

46. A bus subsystem comprising

a memory device and a master device connected in parallel on a bus,

a means for said master device to send a request packet and initiate a bus transaction and

a means for said master device to keep track of current and pending bus transactions,

said bus including a plurality of bus lines for carrying substantially all address, data and control information needed by said memory devices,

said bus containing substantially fewer lines than the number of bits in a single address, and

said bus carrying device-select information without the need for separate device-select lines connected directly to individual devices on said bus, whereby said master device initiates bus transactions which transfer information between devices on said bus and collisions on said bus are

avoided because said master device avoids initiating bus transactions which would conflict with current or pending bus transactions.

5 47. The bus subsystem of claim 46 having at least two of said master devices and including

10 a collision detecting means whereby a first said master device sending a first said request packet can detect a second said master device sending one of said colliding request packets, where one of said said colliding request packet may be sent simultaneous with the initial sending of or overlapping the sending of said first request packet, and

15 an arbitration means whereby said first and said second master devices select a priority order in which each of said master devices will be allowed to access said bus sequentially.

20 48. The bus subsystem of claim 47 wherein each of said master devices has a master ID number and each of said request packets includes a master ID position which is a predetermined number of bits in a predetermined position in said request packet, and wherein said collision detection means comprises

25 a means included in each master device for sending a request packet including said master ID number of said

master device in said master ID position of said request packet and

a means to detect a collision and invoke said arbitration means if any master device detects any other master ID number in said master ID position.

49. The bus subsystem of claim 47 wherein each of said master devices includes

a means for sending a request packet,

a means for driving a selected bus line or lines during at least one selected bus cycle while said request packet is being sent,

a means for monitoring said selected bus line or lines to see if a said master device is sending a colliding request packet and

a means for informing all other master devices that a collision has occurred and for invoking said arbitration means.

50. The bus subsystem of claim 47 wherein each of said master devices includes

a means, when sending a request packet, to drive a selected bus line or lines with a certain current during at least one selected bus cycle,

a means for monitoring said selected bus line or lines for a greater than normal current to see if another master device is driving that line or lines,

a means for detecting said greater than normal current,
and

a means for informing all said master devices that a collision has occurred and for invoking said arbitration means.

51. The bus subsystem of claim 47 wherein said arbitration means comprises

a means for initiating an arbitration cycle,

a means for allocating a single bus line to each master device during at least one selected bus cycle relative to the start of said arbitration cycle,

a means for allocating each master device to a single bus line during one of said selected bus cycles if there are more master devices than available bus lines,

a means for each of said master devices which sent a colliding request packet to drive said bus line allocated to said master device during said selected bus cycle, and

a means in at least one of said master devices for storing information about which master devices sent a colliding request packet,

whereby said master devices can monitor selected bus lines during said arbitration cycle and identify each said master device which sent a colliding request packet.

5 52. The bus subsystem of claim 47 wherein said arbitration means comprises

 a means included in a first one of said master devices which sent colliding request packets for identifying each of said master devices which sent colliding request packets,

10 a means for assigning a priority to each said master device which sent a colliding request packet, and

 a means for allowing each said master device which sent a colliding request packet to access the bus sequentially according to that priority.

15 53. The bus subsystem of claim 52 wherein said priority is based on the physical location of each of said master devices.

20 54. The bus subsystem of claim 52 wherein said priority is based on said master ID number of said master devices.

25 55. The bus subsystem of claim 52 wherein each of said master devices includes a means, when sending a colliding request packet, for deciding which master device can send the next request packet in what order or at what time, whereby no master

device may send a new request packet until responses to each pending request packet have been completed or scheduled.

56. A bus subsystem comprising

5 a plurality of semiconductor devices connected in parallel to a bus,

said bus including a plurality of bus lines for carrying substantially all address, data and control information needed by said semiconductor devices,

10 said control information including device-select information,

said bus containing substantially fewer lines than the number of bits in a single address,

15 said bus carrying said device-select information without the need for separate device-select lines connected directly to individual semiconductor devices,

20 said semiconductor devices including a reset means having an input and an output, the output of the reset means of one semiconductor device being connected to the input of the reset means of the next semiconductor device in series.

57. The bus subsystem of claim 56 further including system reset means comprising

25 a means for generating a first and a second reset signal,

a means for passing said first reset signal to a first of said semiconductor devices and then to subsequent ones of said semiconductor devices in series and

5 a means for passing a second reset signal to said first semiconductor device and then to said subsequent semiconductor devices in series,
said bus subsystem including one of said semiconductor devices containing

10 a device identification register adapted to contain a number unique to said semiconductor device within said bus subsystem,

a device identification register setting means, and
15 a device reset means for resetting said semiconductor device to some desired, known reset state in response to said first reset signal and for setting said device identification register in response to said second reset signal,

20 whereby said bus subsystem can be reset to a known reset state with a unique device identification value in said device identification register of each of said semiconductor devices.

25 58. The bus subsystem of claim 57 wherein said desired, known reset state is where all registers in the semiconductor device are cleared and the state machines are reset.

59. The bus subsystem of claim 57 wherein said device identification register setting means comprises

a means for detecting said second reset signal,

5 a means for reading a device identification number from said bus lines at a specific time relative to said second reset signal and

10 a means for storing said device identification number in said device identification register of said semiconductor device.

60. The bus subsystem of claim 57 wherein said second reset signal comprises multiple pulse sequences and wherein said device identification setting means includes

15 a means for interpreting said pulse sequences as a device identification number and

a means for storing said device identification number in said device identification register of said semiconductor device.

20 61. The bus subsystem of claim 57 wherein said device reset means comprises an n-stage shift register capable of storing n-bit values, wherein said device reset means interprets a specific value in said shift register as said first reset signal and

interprets a specific value in said shift register as said second reset signal.

62. The bus subsystem of claim 57 wherein one of said semiconductor devices is a master device, said master device including a means for generating said first and said second reset signals.

63. The bus subsystem of claim 57 wherein one of said semiconductor devices is a master device, said master device including

a master ID register,

a means for assigning a master ID number to said master device and

a means for storing said master ID number in said master ID register.

64. The bus subsystem of claim 63 further comprising a second one of said master devices, and a means for a first one of said master devices to assign a master ID number to substantially all other said master devices, whereby said first master device assigns one of said master ID numbers to each of said master devices on said bus subsystem and each said master device stores said assigned master ID number in said master ID register.

65. The bus subsystem of claim 57 wherein one of said semiconductor devices includes a device-type register adapted to contain an identifier characteristic of that type of semiconductor device, and one or more modifiable registers, at least one of which is an access-time register adapted for storing access times.

66. The bus subsystem of claim 65 wherein one of said semiconductor devices is a master device having

a means for selecting a semiconductor device,

a means for reading said device-type register of said selected semiconductor device,

a means for determining the device type of said selected semiconductor device,

a means for determining access-time values appropriate for said selected semiconductor device and for storing said access-time values in said access-time registers of said selected semiconductor device, and

a means for selecting and storing other values appropriate for said selected semiconductor device in corresponding registers of said selected semiconductor device,

whereby said master device can select a semiconductor device, determine what type it is, and set said access-time and other registers to contain appropriate values.

67. The bus subsystem of claim 66 further comprising a memory device having at least one discrete memory section and at least one modifiable address register adapted to store memory address information which corresponds to each of said discrete memory sections, and

said master device further comprising a means for selecting and testing each of said discrete memory sections and a means for storing address information in said address registers corresponding to each of said discrete memory sections, whereby said master device can test all said discrete memory sections and assign unique address values thereto.

68. A bus subsystem comprising

two semiconductor devices connected in parallel to a bus, one of said semiconductor devices being a master device,

said bus including a plurality of bus data lines for carrying substantially all address, data and control information needed by said semiconductor devices,

said control information including device-select information,

said bus containing substantially fewer of said bus data lines than the number of bits in a single address, and

said bus carrying device-select information without the need for separate device-select lines connected directly to individual semiconductor devices,

wherein all of said bus data lines are terminated transmission lines and all of said address, data and control information is carried on said bus data lines as a sequential series of bits in the form of low-voltage-swing signals.

69. The bus subsystem of claim 68 further comprising a semiconductor device including a current-mode driver connected to drive one of said bus data lines.

70. The bus subsystem of claim 69 further comprising a semiconductor device having a means to measure the voltage of said low-voltage-swing signals on a selected one of said bus data lines, whereby said semiconductor device can determine whether zero, one, or more than one of said current-mode drivers are driving said selected bus data line.

71. The bus subsystem of claim 70 further comprising a semiconductor device having a plurality of input receivers connected to one of said bus data lines, and

a selection means for selecting said input receivers one by one to sense and store, one at a time, the bits of said sequential series of bits.

5 72. The bus subsystem of claim 70 further comprising a semiconductor device having two input receivers connected to one of said bus data lines.

73. A bus subsystem comprising

10 two semiconductor devices connected in parallel to a bus having a first and a second end, said bus including a bus clock line, said bus clock line having first and second ends corresponding to said first and second ends of said bus, respectively,

15 a clock generator connected to said first end of said bus clock line to generate early bus clock signals with a normal rise time, and

20 signal return means at said second end of said bus clock line to return said early bus clock signals to said first end of said bus as corresponding late bus clock signals,

25 whereby each of said early bus clock signals will propagate from said clock generator along said clock line starting from said first end to said second end of said bus and then return at a later time to said first end of said

bus as a corresponding late bus clock signal, whereby each semiconductor device on said bus can detect said early bus clock signals and said corresponding late bus clock signals.

5 74. The bus subsystem of claim 73 further comprising a first and a second said bus clock line having first and second ends at said first and said second ends of said bus, respectively, wherein said signal return means directly connects said second ends of said first and said second bus clock lines
10 whereby each of said early bus clock signals will propagate from said clock generator at said first end of said bus along said first bus clock line to said second end of said bus and then return on said second bus clock line to said first end of said bus as one of said corresponding late bus clock signals.

15 75. The bus subsystem of claim 73 wherein said signal return means comprises said first bus clock line without a line terminator at said second end thereof whereby each of said early bus clock signals reaching said second end of said first bus
20 clock line will be reflected back along said first bus clock line as said corresponding late bus clock signals.

76. The bus subsystem of claim 73 further comprising
a means for operating said bus in bus cycles timed to
have a certain bus cycle frequency and a corresponding bus
cycle period and

5 a means for operating said clock generator with a
period of twice the bus cycle period.

77. The bus subsystem of claim 76 wherein said bus cycle
frequency is greater than approximately 50 MHz and less than or
10 equal to approximately 500 MHz.

78. The bus subsystem of claim 73 further including a
semiconductor device having an internal device clock generating
means to derive the midpoint time between said early and
15 corresponding late bus clock signals and to generate an internal
device clock synchronized to said midpoint time.

79. The bus subsystem of claim 73 further including a
semiconductor device having a low-skew clock generator circuit
20 comprising

a first delay line having an input, an output and a
basic delay and means for synchronizing the output of said
first delay line with said early bus clock signal,

a second delay line having said basic delay plus a
25 variable delay, said second delay line having an output and

a means for synchronizing the output of said second delay line with said late bus clock signal, and

a third delay line having a third delay and a means to set said third delay midway between the delays of said first and second delay lines, said third delay line having an output which provides an internal device clock signal synchronized to a time halfway between said early and said late bus clock signals.

80. The bus subsystem of claim 73 wherein said early and said late bus clock signals are low-voltage-swing signals that transition cyclically between low and high logical values, and further including a semiconductor device having a low-skew clock generator circuit comprising

a DC amplifier to convert said early and said late bus clock signals into full-swing logic signals,

a first variable delay line having a first variable delay and an input and an output, the input of said first variable delay line being connected to said DC amplifier

a first, a second and a third additional delay line, each having an input and an output, the input of each of said additional delay lines being connected to the output of said first delay line,

said first additional delay line having a fixed delay,

said second additional delay line having said fixed delay plus a second variable delay, and

said third additional delay line having said fixed delay plus one half of said second variable delay,

5 a first clocked input receiver connected to sample said early bus clock signal and gated by said output of said first additional delay line,

10 a means for adjusting said first variable delay so said first clocked input receiver samples said early bus clock signal just as said early bus clock signal transitions,

a second clocked input receiver connected to sample said late bus clock signal and gated by said output of said second additional delay line,

15 a means for adjusting said second variable delay so said second clocked input receiver samples said late bus clock signal just as said late bus clock signal transitions,

20 whereby said output of said third additional delay line is synchronized to a time halfway between said outputs of said first and said second additional delay lines, and said output of said third additional delay line provides an internal device clock signal.

81. The bus subsystem of claim 80 further comprising a semiconductor device having

a first one of said low-skew clock generator circuits which generates a "true" internal device clock signal and

5 a second one of said low-skew clock generator circuits connected to generate a "complement" internal device clock signal synchronized with but opposite in logical value to said "true" internal device clock signal.

10 82. A DRAM device designed to be connected to an external bus having a plurality of bus lines for carrying substantially all address, data and control information needed by said DRAM device as a sequential series of bits, said control information including device-select information, said external bus containing
15 substantially fewer said bus lines than the number of bits in a single address, and said bus carrying device-select information without the need for separate device-select lines connected directly to said DRAM device, said DRAM device comprising

20 an array of memory cells connected in rows and columns, each of said memory cells adapted to store one of said bits, a row address selection means for selecting one of said rows,

a column sense amp connected to each of said columns, each of said column sense amps adapted to latch one of said

bits as a binary logical value or to precharge to a selected state,

5 a column decoding means connected to each of said column sense amps for selecting a plurality of said column sense amps for inputting one of said bits to or outputting one of said bits from said memory cells,

an internal I/O bus having a plurality of internal I/O lines wherein each of said internal I/O lines is connected to a plurality of said column sense amps, and

10 a plurality of bus connection means designed to connect said internal I/O lines to said external bus,

whereby a selected bit of said sequential series of bits can be transferred from said external bus to a selected one of said memory cells or said bit contained in a selected one of said memory cells can be transferred to said external bus.

83. The DRAM device of claim 82 further comprising

20 an output driver connected to one said bus connection means,

an output multiplexer having an output connected to said output driver and a plurality of inputs, each of said inputs being connected to one of said internal I/O lines, and

a control means to select whether said output driver can drive said external bus,

whereby a plurality of memory cells are selected using said row address selection means and said column decoding means and a plurality of bits contained in said plurality of memory cells are output through said column sense amps to said internal I/O bus to said output multiplexer to said output driver to said external bus.

84. The DRAM device of claim 82 further comprising

a plurality of input receivers connected to one of said bus data lines and to said internal I/O bus,

a selection means for selecting said input receivers one by one to sense and store, one at a time, the bits of said sequential series of bits, and

a control means to select whether an input receiver can drive said internal I/O bus, whereby a bit of said sequential series of bits is input from said external bus through one of said input receivers to one of said internal I/O lines to one of said column sense amps to one of said memory cells.

85. The DRAM device of claim 82 further comprising
a first and a second half-array of said memory cells
wherein each said row of said array of said memory cells is
subdivided into two parts,

5 a first and a second one of said internal I/O buses
connected to said column sense amps in said first and said
second half-arrays, respectively, and

10 a column decoder means to gate selected ones of said
column sense amps connected to said memory cells in a
selected row of said first and said second half-arrays
simultaneously.

15 86. The DRAM device of claim 85 wherein said column decoder
means selects sixteen column sense amps at a time.

20 87. The DRAM device of claim 82 wherein said external bus
operates at a certain speed and wherein said DRAM device includes
four of said internal I/O buses, each of which operates at one-
fourth the speed of said external bus.

: 88. The DRAM device of claim 82 further comprising
a means for precharging one of said column sense amps
to a precharged state from which a binary logical value can
quickly be loaded into said column sense amp,

if said column sense amp contains a binary logical value, a means for latching the logical value currently contained in said column sense amp and

a means for instructing said DRAM device to precharge said column sense amp or latch said binary logical value in said column sense amp.

89. The DRAM device of claim 88 further comprising a means for instructing said DRAM device to precharge said column sense amp without further instruction whenever said row address selection means selects a different one of said rows.

90. The DRAM device of claim 88 further comprising a means for instructing said DRAM device to precharge said column sense amp without further instruction at a first or a second preselected time after latching the latest said binary logical value, said first preselected time being long enough for said DRAM to latch said binary logical value into said column sense amp and transfer said binary logical value into memory or onto one of said internal I/O lines, and said second preselected time being a variable which can be stored in said DRAM device whereby said DRAM can latch a binary logical value into said column sense amp for transferring said binary logical value into or out of a selected said memory cell, then precharge to allow a faster subsequent read or write.

91. A package containing

a semiconductor die having a side, circuitry and a plurality of connecting areas positioned along or near said side, spaced at a selected pitch and connected to said circuitry,

said package comprising a plurality of bus connecting means for connecting to a plurality of external bus lines, each of said external bus lines corresponding to one of said connecting areas, each of said bus connecting means being

positioned on a first side of said package, connected to one said external bus line and to said corresponding connecting area on said semiconductor die, and

spaced at a pitch substantially identical to said selected pitch of said connecting areas, whereby each of said external bus lines can be connected to said corresponding connecting area on said semiconductor die by bus connection means positioned along a single side of said package.

92. The package of claim 91 further comprising a plurality of said bus connecting means wherein each of said bus connecting means includes

a pin adapted for connection to one of said external bus lines and

a wire connecting said pin to one of said connecting areas on said semiconductor die,

said wire having an effective lead length less than about 4 millimeters and wherein the effective lead length of said wire of each of said bus connection means for said package is approximately equal.

93. A plurality of packages of claim 91 wherein at least two of said semiconductor die are memory devices, each of said packages being generally flat, having a top and a bottom, and wherein

said packages are physically secured adjacent and parallel to each other in a stack,

where a first one of said packages is adjacent to a second one of said packages in said stack, said top of said first package is substantially aligned with said bottom of said second package, and

said bus connecting means of each of said packages are substantially aligned and are lying substantially in a plane.

94. The plurality of packages of claim 93 further comprising a plurality of stacks wherein each of said bus connecting means can be electrically connected to corresponding said bus connecting means in each of said stacks.

95. A semiconductor device capable of use in a semiconductor bus architecture including a plurality of semiconductor devices connected in parallel to a bus wherein said bus includes a plurality of bus lines for carrying substantially all address, data, control and device-select information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said bus, and has substantially fewer bus lines than the number of bits in a single address, and carries device-select information for said semiconductor device without the need for a separate device-select line connected directly to said individual semiconductor device, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said bus, and

at least one modifiable identification register accessible to said bus through said connection means, whereby data may be transmitted to said register via said bus and enable said device thereafter to be uniquely identified.

96. The semiconductor device of claim 95 wherein said semiconductor device is a memory device which connects substantially only to said bus and sends and receives substantially all address, data and control information over said bus.

97. A semiconductor device capable of use in a semiconductor bus architecture including a plurality of semiconductor devices connected in parallel to a bus wherein said bus includes a plurality of bus lines for carrying substantially all address, data, control and device-select information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said bus, and has substantially fewer bus lines than the number of bits in a single address, and carries device-select information for said semiconductor device without the need for a separate device-select line connected directly to said individual semiconductor device, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said bus, and

at least one modifiable register to hold device address information, said modifiable register accessible to said bus through said connection means, whereby data may be transmitted to said register via said bus which enables said device thereafter to respond to a predetermined range of addresses.

98. The semiconductor device of claim 97 wherein said semiconductor device is a memory device which connects substantially only to said bus and sends and receives

substantially all address, data and control information over said bus.

99. The semiconductor device of claim 98 wherein said memory device has at least one discrete memory section and also has at least one modifiable address register adapted to store memory address information which corresponds to each said discrete memory section.

100. The semiconductor device of claim 99 wherein said memory address information comprises a pointer to said discrete memory section.

101. The semiconductor device of claim 100 wherein said discrete memory section has a top and a bottom and said memory address information comprises pointers to said top and said bottom.

102. The semiconductor device of claim 100 wherein said memory address information comprises
a pointer to said discrete memory section and
a range value indicating the size of said discrete memory section.

103. A semiconductor device capable of use in a semiconductor bus architecture including a plurality of semiconductor devices connected in parallel to a bus wherein said bus includes a plurality of bus lines for carrying substantially all address, data and control information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said bus, and has substantially fewer bus lines than the number of bits in a single address, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said bus, and

at least one modifiable access-time register accessible to said bus through said connection means, whereby data may be transmitted to said register via said bus which establishes a predetermined amount of time that said semiconductor device thereafter must wait before using said bus in response to a request.

104. The semiconductor device of claim 103 wherein said semiconductor device is a memory device which connects substantially only to said bus and sends and receives substantially all address, data and control information over said bus.

105. The semiconductor device of claim 103 further comprising at least two access-time registers and one of said access-time registers is permanently programmed to contain a fixed value and at least one of said access-time registers can be modified by information carried on said bus.

106. A semiconductor device capable of use in a semiconductor bus architecture including a plurality of semiconductor devices connected in parallel to a bus wherein said bus includes a plurality of bus lines for carrying substantially all address, data, control and device-select information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said bus, and has substantially fewer bus lines than the number of bits in a single address, and carries device-select information for said semiconductor device without the need for a separate device-select line connected directly to said individual semiconductor device, and wherein each said bus line is a terminated transmission line, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said bus, and

a bus line driver capable of producing a low-voltage-swing signal on one of said terminated transmission lines.

107. The semiconductor device of claim 106 wherein said semiconductor device is a memory device which connects substantially only to said bus and sends and receives substantially all address, data and control information over said bus.

108. A semiconductor device capable of use in a semiconductor bus architecture including a plurality of semiconductor devices connected in parallel to a bus wherein said bus includes a plurality of bus lines for carrying substantially all address, data, control and device-select information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said bus, and has substantially fewer bus lines than the number of bits in a single address, and carries device-select information for said semiconductor device without the need for a separate device-select line connected directly to said individual semiconductor device, said bus further including at least one bus clock line for carrying early and late bus clock signals, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said bus, and

an internal device clock generating means which generates an internal device clock synchronized to a time halfway between said early and said late bus clock signals.

109. The semiconductor device of claim 108 wherein said bus further includes a first and a second one of said bus clock lines, said first bus clock line carries said early bus clock signal and said second bus clock line carries said late bus clock signal, said semiconductor device further comprising a means to detect said early bus clock signal on said first bus clock line and a means to detect said late bus clock signal on said second bus clock line.

110. The semiconductor device of claim 109 wherein said semiconductor device is a memory device which connects substantially only to said bus and sends and receives substantially all address, data and control information over said bus.

111. A semiconductor device capable of use in a semiconductor bus architecture including a plurality of semiconductor devices connected in parallel to a bus wherein said bus includes a plurality of bus lines for carrying as a sequential series of bits substantially all address, data, control and device-select information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said bus, and has substantially fewer bus lines than the number of bits in a single address, and carries device-select information for said semiconductor device without the need for a

separate device-select line connected directly to said individual semiconductor device, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said bus,

5 a plurality of input receivers connected to one of said bus data lines and

a selection means for selecting said input receivers one by one to sense and store, one at a time, the bits of said sequential series of bits.

10 112. The semiconductor device of claim 111 wherein said semiconductor device is a memory device which connects substantially only to said bus and sends and receives substantially all address, data and control information over said
15 bus.

113. The semiconductor device of claim 112 wherein two input receivers are connected to one of said bus lines.

20 114. A semiconductor device capable of use in an architecture for a semiconductor system bus including a plurality of semiconductor devices connected in parallel to a bus wherein said bus system includes a plurality of bus lines for carrying
25 substantially all address, data, control and device-select information needed by said semiconductor device for communication

with substantially every other semiconductor device connected to said system bus, and has substantially fewer bus lines than the number of bits in a single address, and carries device-select information for said semiconductor device without the need for a
5 separate device-select line connected directly to said individual semiconductor device, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said system bus,

an internal input/output bus within said semiconductor device having more lines than said system bus, and
10

a means for multiplexing the lines of said internal bus to the lines of said system bus, whereby said system bus can run at a higher speed than said internal bus.

115. The semiconductor device of claim 114 wherein said
15 semiconductor device is a memory device which connects substantially only to said system bus and sends and receives substantially all address, data and control information over said system bus.

20 116. A semiconductor device capable of use in an architecture for a semiconductor system bus including a plurality of semiconductor devices connected in parallel to a bus wherein said system bus includes a plurality of bus lines for carrying
25 substantially all address, data, control and device-select

information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said system bus, and has substantially fewer bus lines than the number of bits in a single address, and carries device-select information for said semiconductor device without the need for a separate device-select line connected directly to said individual semiconductor device, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said system bus,

an internal input/output bus within said semiconductor device having more lines than said system bus,

a means for multiplexing the lines of said internal bus to the lines of said system bus, whereby said system bus can run at a higher speed than said internal bus, and

at least one modifiable identification register accessible to said system bus through said connection means, whereby data may be transmitted to said register via said system bus and which enables said device thereafter to be uniquely identified.

117. The semiconductor device of claim 116 wherein said semiconductor device is a memory device which connects substantially only to said system bus and sends and receives substantially all address, data and control information over said system bus.

118. A semiconductor device capable of use in an architecture for a semiconductor system bus including a plurality of semiconductor devices connected in parallel to a bus wherein said system bus includes a plurality of bus lines for carrying substantially all address, data, control and device-select information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said system bus, and has substantially fewer bus lines than the number of bits in a single address, and carries device-select information for said semiconductor device without the need for a separate device-select line connected directly to said individual semiconductor device, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said system bus,

an internal input/output bus within said semiconductor device having more lines than said system bus,

a means for multiplexing the lines of said internal bus to the lines of said system bus, whereby said system bus can run at a higher speed than said internal bus, and

at least one modifiable register to hold device address information, said modifiable register accessible to said system bus through said connection means, whereby data may be transmitted to said register via said system bus which enables said device thereafter to respond to a predetermined range of addresses.

119. The semiconductor device of claim 118 wherein said semiconductor device is a memory device which connects substantially only to said system bus and sends and receives substantially all address, data and control information over said system bus.

120. The semiconductor device of claim 119 wherein said memory device has at least one discrete memory section and also has at least one modifiable address register adapted to store memory address information which corresponds to each said discrete memory section.

121. A semiconductor device capable of use in an architecture for a semiconductor system bus including a plurality of semiconductor devices connected in parallel to a bus wherein said system bus includes a plurality of bus lines for carrying substantially all address, data and control information needed by said semiconductor device for communication with substantially every other semiconductor device connected to said system bus, and has substantially fewer bus lines than the number of bits in a single address, said semiconductor device comprising

connection means adapted to connect said semiconductor device to said system bus,

an internal input/output bus within said semiconductor device having more lines than said system bus,

a means for multiplexing the lines of said internal bus to the lines of said system bus, whereby said system bus can run at a higher speed than said internal bus, and

at least one modifiable access-time register accessible to said system bus through said connection means, whereby data may be transmitted to said register via said system bus which establishes a predetermined amount of time that said semiconductor device thereafter must wait before using said system bus in response to a request.

122. The semiconductor device of claim 121 wherein said semiconductor device is a memory device which connects substantially only to said system bus and sends and receives substantially all address, data and control information over said system bus.

123. The semiconductor device of claim 121 further comprising at least two access-time registers and one of said access-time registers is permanently programmed to contain a fixed value and at least one of said access-time registers can be modified by information carried on said system bus.

124. A semiconductor device capable of use in a semiconductor bus architecture including a plurality of semiconductor devices connected in parallel to a bus wherein said bus includes

5 a plurality of bus lines for carrying substantially all address,
data, control and device-select information needed by said
semiconductor device for communication with substantially every
other semiconductor device connected to said bus, and has
10 substantially fewer bus lines than the number of bits in a single
address, and carries device-select information for said
semiconductor device without the need for a separate device-
select line connected directly to said individual semiconductor
device, wherein said address, data, control and device-select
15 information is carried over said bus in the form of request
packets and bus transactions, said semiconductor device
comprising

connection means adapted to connect said semiconductor
device to said bus,

15 a means to receive said request packets over said bus,

a means to decode information in said request packets,

and

a means to respond to said information in said request
packets.

20 125. The semiconductor device of claim 124 wherein said
means to decode information in said request packet further
comprises

a means to identify and decode said control information
25 in said request packet,

a means to identify and decode said device-select information in said request packet,

a means to identify and decode said address information in said request packet and

5 a means to determine whether said control information or said address information instructs said semiconductor device to begin a response.

10 126. The semiconductor device of claim 124 wherein each of said bus transactions is carried out in response to said address and said control information in one of said request packets, and wherein said means to identify and decode information in said request packets includes a means to identify a sequence of bytes on said bus as one of said request packets containing said
15 address and said control information, said control information including information about the type of said bus transaction being requested and the access time which needs to intervene before beginning said bus transaction over said bus and said address and said control information includes device-select
20 information instructing one or more said semiconductor devices to respond to said address and said control information.

127. The semiconductor device of claim 124 further comprising

a plurality of sense amplifiers adapted to precharge to a selected state or to latch a bit of information,

a means to hold said sense amplifiers in an unmodified state after latching one of said bits of information,

5 a means to precharge said sense amplifiers and

a means for selecting whether said semiconductor device should precharge said sense amplifiers or should hold said sense amplifiers in an unmodified state.

10 128. The semiconductor device of claim 124 wherein said means to respond to said information, where said information is control information, further comprises a means to

transfer a data block during a data block transfer, further including a means to

15 read data from said semiconductor device and

write data into said semiconductor device, and

initiate a data block transfer,

transfer a data block of a selected size,

transfer a data block at a selected time,

20 access a control register, including a means to read

from or write to said control register, or

select normal or page-mode access.

129. The semiconductor device of claim 124 further
25 comprising a means to respond to said information in said request

packet if said information includes a device identification number unique to said semiconductor device.

130. The semiconductor device of claim 124 further comprising a means to respond to said information in said request packet if said information includes a special device identification number which calls for said semiconductor device to respond.

131. The semiconductor device of claim 124 further comprising a means to respond to said information in said request packet if said information includes an address unique to said semiconductor device.

132. The semiconductor device of claim 124 further comprising a means to interpret said control information and decode the time to wait before beginning said bus transaction over said bus.

133. The semiconductor device of claim 124 further comprising a means to interpret said control information and decode the size of a data block to transfer during one of said bus transactions.

134. The semiconductor device of claim 124, 125, 126, 127,
128, 129, 130, 131, 132 or 133 wherein said semiconductor device
is a memory device which connects substantially only to said bus
and sends and receives substantially all address, data and
control information over said bus.

135. A semiconductor device capable of use in a semi-
conductor bus architecture including a plurality of semiconductor
devices connected in parallel to a bus wherein said bus includes
a plurality of bus lines for carrying substantially all address,
data, control and device-select information needed by said
semiconductor device for communication with substantially every
other semiconductor device connected to said bus, and has
substantially fewer bus lines than the number of bits in a single
address, and carries device-select information for said
semiconductor device without the need for a separate device-
select line connected directly to said individual semiconductor
device, wherein said address, data, control and device-select
information is carried over said bus in the form of request
packets and bus transactions, said semiconductor device
comprising

connection means adapted to connect said semiconductor
device to said bus,

a means to encode address and control information in
said request packets and

a means to send said request packets over said bus.

136. The semiconductor device of claim 135 further comprising a means to request a bus transaction wherein each of
5 said bus transactions is carried out in response to said address and said control information in one of said request packets, and wherein said means to encode information in said request packets includes a means to mark a sequence of bytes on said bus as one of said request packets, said control information including
10 information about the type of said bus transaction being requested and the access time which needs to intervene before beginning said bus transaction over said bus and said address and said control information includes device-select information instructing one or more said semiconductor devices to respond to
15 said address and said control information.

137. The semiconductor device of claim 135 wherein one or more of said plurality of semiconductor devices has a unique device identification number, said semiconductor device further
20 comprising a means to send control information to a specific one of said plurality of semiconductor devices by including in said request packet a selected said device identification number.

138. The semiconductor device of claim 135 wherein each of
25 said plurality of semiconductor devices is adapted to respond to

a special device identification number, said semiconductor device further comprising a means to send control information to each of said plurality of semiconductor devices by including in said request packet said special device identification number.

5

139. The semiconductor device of claim 135 wherein one or more of said plurality of semiconductor devices is a memory device having a plurality of addresses, said semiconductor device further comprising a means to send control information to a specific address or range of addresses in one of said plurality of semiconductor devices by including said specific address or range of addresses in said request packet.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500

140. The semiconductor device of claim 135 wherein at least one of said request packets is a request packet requesting a bus transaction which is followed by a corresponding one of said bus transactions, said semiconductor device further comprising a means to encode said control information to specify directly or indirectly the time between the end of said request packet requesting a bus transaction and said corresponding bus transaction over said bus.

141. The semiconductor device of claim 140 wherein one type of said bus transactions is a transfer of a data block, said semiconductor device further comprising a means to encode said

25

control information to specify the size of said data block to transfer.

142. The semiconductor device of claim 140 further comprising a means to keep track of current and pending bus transactions, whereby collisions on said bus are avoided because said semiconductor device avoids initiating bus transactions which would conflict with current or pending bus transactions.

143. The semiconductor device of claim 135 wherein said semiconductor device is a first master device and one of said plurality of semiconductor devices is a second master device, further comprising

a collision detecting means whereby said first master device when sending a first one of said request packets can detect said second master device sending a colliding one of said request packets, where said colliding request packet may be sent simultaneous with the initial sending of or overlapping the sending of said first request packet, and

an arbitration means whereby said first and said second master devices select a priority order in which each of said master devices will be allowed to access said bus sequentially.

144. The semiconductor device of claim 143 wherein said semiconductor device is a master device and at least one of said plurality of semiconductor devices is a master device, each of said master devices has a master ID number and each of said request packets includes a master ID position which is a predetermined number of bits in a predetermined position in said request packet, and wherein said collision detection means comprises

a means for said semiconductor device to send its master ID number in said request packet and

a means to detect a collision and invoke said arbitration means if said semiconductor device detects any other master ID number in said master ID position.

145. The semiconductor device of claim 144 wherein said system bus architecture includes a means for carrying information on said bus during bus cycles, said semiconductor device further comprising

a means for driving a selected bus line or lines during at least one selected bus cycle while sending each said request packet,

a means for monitoring said selected bus line or lines to see if another said master device is sending one of said colliding request packets and

a means for informing all said master devices that a collision has occurred and for invoking said arbitration means.

5 146. The semiconductor device of claim 145 further comprising

a means, when sending a request packet, for driving a selected bus line or lines with a certain current during at least one selected bus cycle,

10 a means for monitoring said selected bus line or lines for a greater than normal current to see if another said master device is driving that line or lines,

a means for detecting said greater than normal current, and

15 a means for informing all said master devices that a collision has occurred and for invoking said arbitration means.

20 147. The semiconductor device of claim 143 wherein said arbitration means comprises

a means for initiating an arbitration cycle,

a means for allocating a single bus line to each said master device during at least one selected bus cycle relative to the start of said arbitration cycle,

a means for allocating each said master device to a single bus line during one of said selected bus cycles if there are more master devices than available bus lines,

a means for each of said master devices which sent one of said colliding request packets to drive said bus line allocated to said master device during said selected bus cycle, and

a means in at least one of said master devices for storing information about which master devices sent one of said colliding request packets,

whereby said master devices can monitor selected bus lines during said arbitration cycle and identify each said master device which sent one of said colliding request packets.

148. The semiconductor device of claim 143 wherein said arbitration means comprises

a means for identifying each of said master devices which sent one of said colliding request packets,

a means for assigning a priority to each said master device which sent one of said colliding request packets, and

a means for allowing each said master device which sent one of said colliding request packets to access the bus sequentially according to that priority.

149. The semiconductor device of claim 143 wherein said priority is based on the physical location of each of said master devices.

5 150. The semiconductor device of claim 143 wherein said priority is based on said master ID number of said master devices.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228